

Description

diameter: 5/32", grip range: 0.438" - 0.500", flush head, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3522-5-8](#)

SKU / Model:	CR3522508
Minimum Qty (MOQ):	100
NSN:	5320-01-396-5261
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N CR3522-5-08 Specifications

Fastener Length:	0.840 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy R-405 Sleeve
Material:	Iron Alloy 660 Locking Ring Or Aluminum Alloy 5056 Locking Ring
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Locking Ring Or Qq-a-430 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Ams5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve
Surface Treatment:	Passivate Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Specification/standard Data:	81349-mil-r-7885/5c Government Specification

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522-5-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.