

# P/N CR3522-5-10

## **Description**

diameter: 5/32", grip range: 0.563" - 0.625", flush head, monel sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

#### **Additional Information**

SKU / Model: CR3522510

Minimum Qty (MOQ): 100

NSN: 5320-01-150-2748

ECCN: EAR99









# P/N CR3522-5-10 Specifications

Fastener Length:	0.960 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.157 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.286 Inches Nominal
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.563 Inches Minimum And 0.625 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Alloy Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem
Material Document And Classification:	Ams5657 Assn Std 3rd Material Response Stem
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec 2nd Material Response Sleeve

### **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR3522-5-10">https://military-fasteners.com/rivets/blind+rivets/CR3522-5-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.