

**Description**

diameter: 3/16", grip range: 0.376" - 0.437", flush head, monel sleeve, 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3522-6-7](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR3522607                                   |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-379-5131                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3522-6-07 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.545 Inches Minimum And 0.575 Inches Maximum                                  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.188 Inches Minimum And 0.192 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.313 Inches Minimum And 0.345 Inches Maximum                                  |
| <b>Expansion Device:</b>                              | Knob Stem-type K   |
| <b>Grip Length:</b>                                   | 0.376 Inches Minimum And 0.437 Inches Maximum                                  |
| <b>Features Provided:</b>                             | Self-locking   |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal  |
| <b>Material:</b>                                      | Iron Alloy 660 Locking Ring  |
| <b>Material:</b>                                      | Nickel Alloy 400 Sleeve  |
| <b>Material:</b>                                      | Steel Comp 632 Stem  |
| <b>Material Document And Classification:</b>          | Ams 5657 Assn Std Single Material Response Stem                                |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Locking Ring                        |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec Single Material Response Sleeve                              |
| <b>Surface Treatment:</b>                             | Passivate Locking Ring   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Locking Ring                        |
| <b>Specification/standard Data:</b>                   | 80205-nas9308 Professional/industrial Association Standard                     |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522-6-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.