

**Description**

diameter: 3/16", grip range: 0.376" - 0.437", flush head, monel sleeve, 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3522-6-7](#)

SKU / Model:	CR3522607
Minimum Qty (MOQ):	100
NSN:	5320-01-379-5131
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N CR3522-6-07 Specifications

<b>Fastener Length:</b>	0.545 Inches Minimum And 0.575 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.192 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.313 Inches Minimum And 0.345 Inches Maximum
<b>Expansion Device:</b>	Knob Stem-type K
<b>Grip Length:</b>	0.376 Inches Minimum And 0.437 Inches Maximum
<b>Features Provided:</b>	Self-locking
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Iron Alloy 660 Locking Ring
<b>Material:</b>	Nickel Alloy 400 Sleeve
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Passivate Locking Ring
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
<b>Specification/standard Data:</b>	80205-nas9308 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522-6-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.