

Description

Diameter: 3/16", grip range: 0.313" - 0.375", flush head, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3522-6-06](#)

SKU / Model:	CR352266
Minimum Qty (MOQ):	100
NSN:	5320-01-150-2752
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N CR3522-6-6 Specifications

Fastener Length:	0.760 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.189 Inches Nominal
Head Major Diameter:	0.353 Inches Nominal
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Alloy Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem
Material Document And Classification:	Ams5657 Assn Std 3rd Material Response Stem
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec 2nd Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.