

Description

Diameter: 3/16", grip range: 0.313" - 0.375", flush head, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3522-6-06](#)

| | |
|-------------------------|---|
| SKU / Model: | CR352266 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-150-2752 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N CR3522-6-6 Specifications

| | |
|--|--|
| Fastener Length: | 0.760 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.189 Inches Nominal |
| Head Major Diameter: | 0.353 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Nickel Alloy Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Corrosion Resisting Stem |
| Material Document And Classification: | Ams5657 Assn Std 3rd Material Response Stem |
| Material Document And Classification: | Ams5731 Assn Std 1st Material Response Locking Ring |
| Material Document And Classification: | Qq-n-281 Fed Spec 2nd Material Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.