

**Description**

diameter: 3/16", grip range: 0.188" - 0.250", 100°, flush head - monel sleeve - 15-7 ph corrosion resistant stem- sleeve has aluminum coating (p)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | CR3522P604       |
| Minimum Qty (MOQ): | 100              |
| NSN:               | 5320-01-613-4275 |



## P/N CR3522P6-04 Specifications

|                             |  |
|-----------------------------|--|
| <b>Fastener Length:</b>     | 0.250 Inches Minimum   |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.189 Inches Nominal   |
| <b>Shank Style:</b>         | Self-plugging  |
| <b>Head Major Diameter:</b> | 0.353 Inches Nominal   |
| <b>Countersink Angle:</b>   | 100.0 Degrees Nominal  |
| <b>Material:</b>            | Nickel Alloy Sleeve  |
| <b>Material:</b>            | Steel Corrosion Resisting Mechanical Lock                                      |
| <b>Material:</b>            | Steel Corrosion Resisting Stem   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522P6-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.