

Description

diameter: 3/16", grip range: 0.251" - 0.312", 100°, flush head - monel sleeve - 15-7 ph corrosion resistant stem- sleeve has aluminum coating (p)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | CR3522P605 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-221-6920 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N CR3522P6-05 Specifications

| | |
|---|--|
| Fastener Length: | 0.420 Inches Minimum And 0.450 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.069 Inches Nominal |
| Shank Diameter: | 0.188 Inches Minimum And 0.192 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.349 Inches Minimum And 0.357 Inches Maximum |
| Expansion Device: | Break Stem |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Special Features: | Min Blind Clearance 0.415/hole Limits 0.192-0.196 |
| Material: | Nickel Alloy R-405 Sleeve |
| Material: | Iron Alloy 660 Locking Ring |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams 5657 Assn Std 2nd Material Response Stem |
| Material Document And Classification: | Ams 5731 Assn Std 3rd Material Response Locking Ring |
| Material Document And Classification: | Qq-n-281 Fed Spec 1st Material Response Sleeve |
| Surface Treatment: | Aluminum Sleeve |
| Surface Treatment Document And Classification: | C-123 Mfr Ref Single Treatment Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522P6-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.