

**Description**

diameter: 3/16", grip range: 0.251" - 0.312", 100°, flush head - monel sleeve - 15-7 ph corrosion resistant stem- sleeve has aluminum coating (p)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	CR3522P605
Minimum Qty (MOQ):	100
NSN:	5320-01-221-6920
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N CR3522P6-05 Specifications

<b>Fastener Length:</b>	0.420 Inches Minimum And 0.450 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.069 Inches Nominal
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.192 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Expansion Device:</b>	Break Stem
<b>Grip Length:</b>	0.251 Inches Minimum And 0.312 Inches Maximum
<b>Special Features:</b>	Min Blind Clearance 0.415/hole Limits 0.192-0.196
<b>Material:</b>	Nickel Alloy R-405 Sleeve
<b>Material:</b>	Iron Alloy 660 Locking Ring
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std 3rd Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec 1st Material Response Sleeve
<b>Surface Treatment:</b>	Aluminum Sleeve
<b>Surface Treatment Document And Classification:</b>	C-123 Mfr Ref Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522P6-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.