

Description

diameter: 3/16", grip range: 0.376" - 0.437", 100°, flush head - monel sleeve - 15-7 ph corrosion resistant stem- sleeve has aluminum coating (p)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3522P607
Minimum Qty (MOQ):	100
NSN:	5320-01-388-2575



\* See page 2 for technical characteristics

## P/N CR3522P6-07 Specifications

<b>Fastener Length:</b>	0.820 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.192 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.353 Inches Nominal
<b>Grip Length:</b>	0.376 Inches Minimum And 0.437 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Nickel Sleeve
<b>Surface Treatment:</b>	Aluminum Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522P6-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.