

## Description

diameter: 1/8", grip range: 0.025" - 0.062", universal head, monel sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

## Additional Information

### Alternate Part Numbers

[CR3523-4-1](#)

SKU / Model:	CR3523401
Minimum Qty (MOQ):	100
NSN:	5320-01-480-1646
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N CR3523-4-01 Specifications

<b>Fastener Length:</b>	0.161 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.125 Inches Minimum And 0.129 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.025 Inches Minimum And 0.062 Inches Maximum
<b>Material:</b>	Nickel Alloy R-405 Sleeve
<b>Material:</b>	Iron Alloy 660 Mechanical Lock
<b>Material:</b>	Steel Comp 632 Stem Or Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std 1st Material Response Stem Or Ams 5737 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Mechanical Lock
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.