

Description

diameter: 1/8", grip range: 0.025" - 0.062", universal head, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3523-4-1](#)

SKU / Model:	CR3523401
Minimum Qty (MOQ):	100
NSN:	5320-01-480-1646
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N CR3523-4-01 Specifications

Fastener Length:	0.161 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.025 Inches Minimum And 0.062 Inches Maximum
Material:	Nickel Alloy R-405 Sleeve
Material:	Iron Alloy 660 Mechanical Lock
Material:	Steel Comp 632 Stem Or Iron Alloy 660 Stem
Material Document And Classification:	Ams 5657 Assn Std 1st Material Response Stem Or Ams 5737 Assn Std 2nd Material Response Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Mechanical Lock
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.