

**Description**

diameter: 1/8", grip range: 0.063" - 0.125", universal head, monel sleeve, corrosion resistant stem, CR3523 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3523-4-2](#)

SKU / Model:	CR3523402
Minimum Qty (MOQ):	100
NSN:	5320-01-163-0178
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR3523-4-02 Specifications

<b>Fastener Length:</b>	0.450 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.125 Inches Minimum And 0.129 Inches Maximum
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Minimum Tensile Strength:</b>	400 Pounds Per Square Inch
<b>Shear Strength:</b>	646 Single Pounds Per Square Inch
<b>Material:</b>	Nickel Alloy Sleeve
<b>Material:</b>	Iron Alloy 660 Locking Ring
<b>Material:</b>	Steel Stem
<b>Material Document And Classification:</b>	Ams5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.