

Description

diameter: 1/8", grip range: 0.188" - 0.250", universal head, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3523-4-4](#)

| | |
|-------------------------|---|
| SKU / Model: | CR3523404 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-152-8668 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N CR3523-4-04 Specifications

| | |
|--|---|
| Fastener Length: | 0.570 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Nominal |
| Shank Diameter: | 0.126 Inches Nominal |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.250 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Material: | Nickel Alloy Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Corrosion Resisting Stem |
| Material Document And Classification: | Ams5657 Assn Std 3rd Material Response Stem |
| Material Document And Classification: | Ams5731 Assn Std 1st Material Response Locking Ring |
| Material Document And Classification: | Qq-n-281 Fed Spec 2nd Material Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.