

Description

diameter: 1/8", grip range: 0.438" - 0.500", universal head, monel sleeve, corrosion resistant stem, CR3523 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3523-4-8](#)

SKU / Model:	CR3523408
Minimum Qty (MOQ):	100
NSN:	5320-01-373-7308
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N CR3523-4-08 Specifications

Fastener Length:	0.599 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Material:	Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve Steel Comp 632 Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeveams 5657 Assn Std Single Material Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-4-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.