

**Description**

diameter: 5/32", grip range: 0.126" - 0.187", universal head, monel sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

CR3523-5-3

SKU / Model:	CR3523503
Minimum Qty (MOQ):	100
NSN:	5320-01-134-8771
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N CR3523-5-03 Specifications

<b>Fastener Length:</b>	0.283 Inches Minimum And 0.303 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.156 Inches Minimum And 0.160 Inches Maximum
<b>Head Major Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Material:</b>	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.