

Description

diameter: 5/32", grip range: 0.251" - 0.312", universal head, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3523-5-5](#)

SKU / Model:	CR3523505
Minimum Qty (MOQ):	100
NSN:	5320-01-155-9855
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N CR3523-5-05 Specifications

Fastener Length:	0.408 Inches Minimum And 0.428 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Material:	Nickel Alloy 400 Sleeve
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-5-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.