

Description

diameter: 5/32", grip range: 0.438" - 0.50", universal head, monel sleeve, corrosion resistant stem, CR3523 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[NAS9307M5-08](#) [CR3523-5-8](#)

| | |
|--------------------|------------------|
| SKU / Model: | CR3523508 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-153-1253 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N CR3523-5-08 Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.840 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Nominal |
| Shank Diameter: | 0.157 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.312 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.438 Inches Minimum And 0.500 Inches Maximum |
| Material: | Nickel Alloy Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Corrosion Resisting Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-5-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.