

**Description**

diameter: 5/32", grip range: 0.438" - 0.50", universal head, monel sleeve, corrosion resistant stem, CR3523 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[NAS9307M5-08](#) [CR3523-5-8](#)

SKU / Model:	CR3523508
Minimum Qty (MOQ):	100
NSN:	5320-01-153-1253
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N CR3523-5-08 Specifications

<b>Fastener Length:</b>	0.840 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Nominal
<b>Shank Diameter:</b>	0.157 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.312 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.438 Inches Minimum And 0.500 Inches Maximum
<b>Material:</b>	Nickel Alloy Sleeve
<b>Material:</b>	Steel Corrosion Resisting Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-5-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.