

Description

diameter: 5/32", grip range: 0.563" - 0.625", universal head, monel sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3523510
Minimum Qty (MOQ):	100
NSN:	5320-01-152-8679
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N CR3523-5-10 Specifications

<b>Fastener Length:</b>	0.960 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Nominal
<b>Shank Diameter:</b>	0.157 Inches Nominal
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.312 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.563 Inches Minimum And 0.625 Inches Maximum
<b>Material:</b>	Nickel Alloy Sleeve
<b>Material:</b>	Steel Corrosion Resisting Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Stem
<b>Material Document And Classification:</b>	Ams5657 Assn Std 3rd Material Response Stem
<b>Material Document And Classification:</b>	Ams5731 Assn Std 1st Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec 2nd Material Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.