

Description

length: 0.70", universal head, serrated stem,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3523-6-9](#)

SKU / Model:	CR3523609
Minimum Qty (MOQ):	100
NSN:	5320-01-374-0502
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



P/N CR3523-6-09 Specifications

Fastener Length:	0.700 Inches Nominal
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.192 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Material:	Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve Steel Comp 632 Stem
Material Document And Classification:	Qq0n0281 Fed Spec All Material Responses Sleeveams 5657 Assn Std Single Material Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-6-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.