

Description

Fastener Length: 1-1/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR3523611
Minimum Qty (MOQ):	100
NSN:	5320-01-152-8690
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N CR3523-6-11 Specifications

Fastener Length:	1.070 Inches Nominal
Head Style:	Universal
Head Height:	0.080 Inches Nominal
Shank Diameter:	0.189 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.375 Inches Nominal
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.626 Inches Minimum And 0.687 Inches Maximum
Material:	Nickel Alloy Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem
Material Document And Classification:	Ams5657 Assn Std 3rd Material Response Stem
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec 2nd Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-6-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.