

Description

CR3523 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3523-6-06](#)

| | |
|-------------------------|--|
| SKU / Model: | CR352366 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-197-6642 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N CR3523-6-6 Specifications

| | |
|--|--|
| Fastener Length: | 0.482 Inches Minimum And 0.512 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.188 Inches Minimum And 0.192 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Material: | Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.