

# P/N CR3523-6-9

### **Description**

CR3523-6-9 Blind Rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

CR3523-6-09

SKU / Model: CR352369

Minimum Qty (MOQ): 100

NSN: 5320-01-374-0502

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# **P/N CR3523-6-9 Specifications**

Fastener Length:	0.700 Inches Nominal
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.192 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Material:	Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleevesteel Comp 632 Stem
Material Document And Classification:	Qq0n0281 Fed Spec All Material Responses Sleeveams 5657 Assn Std Single Material Response Stem

# **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR3523-6-9">https://military-fasteners.com/rivets/blind+rivets/CR3523-6-9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.