

**Description**

CR3523-6-9 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3523-6-09](#)

SKU / Model:	CR352369
Minimum Qty (MOQ):	100
NSN:	5320-01-374-0502
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N CR3523-6-9 Specifications

<b>Fastener Length:</b>	0.700 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.192 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.501 Inches Minimum And 0.562 Inches Maximum
<b>Material:</b>	Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Qq0n0281 Fed Spec All Material Responses Sleeveams 5657 Assn Std Single Material Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523-6-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.