

## Description


diameter: 1/8", grip range: 0.037" - 0.062", universal head - monel sleeve - 15-7 ph corrosion resistant stem- sleeve has aluminum coating (p)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	CR3523P401
Minimum Qty (MOQ):	100
NSN:	5320-01-222-2492
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR3523P4-01 Specifications

<b>Fastener Length:</b>	0.131 Inches Minimum And 0.161 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.125 Inches Minimum And 0.129 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Expansion Device:</b>	Break Stem
<b>Grip Length:</b>	0.025 Inches Minimum And 0.062 Inches Maximum
<b>Special Features:</b>	Min Blind Clearance 0.355/hole Limits 0.129-0.132
<b>Material:</b>	Nickel Alloy R-405 Sleeve
<b>Material:</b>	Iron Alloy 660 Locking Ring
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std 3rd Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec 1st Material Response Sleeve
<b>Surface Treatment:</b>	Aluminum Sleeve
<b>Surface Treatment Document And Classification:</b>	C-123 Mfr Ref Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523P4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.