

Description

diameter: 1/8", grip range: 0.037" - 0.062", universal head - monel sleeve - 15-7 ph corrosion resistant stem- sleeve has aluminum coating (p)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3523P401
Minimum Qty (MOQ):	100
NSN:	5320-01-222-2492
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N CR3523P4-01 Specifications

Fastener Length:	0.131 Inches Minimum And 0.161 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Break Stem
Grip Length:	0.025 Inches Minimum And 0.062 Inches Maximum
Special Features:	Min Blind Clearance 0.355/hole Limits 0.129-0.132
Material:	Nickel Alloy R-405 Sleeve
Material:	Iron Alloy 660 Locking Ring
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std 2nd Material Response Stem
Material Document And Classification:	Ams 5731 Assn Std 3rd Material Response Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec 1st Material Response Sleeve
Surface Treatment:	Aluminum Sleeve
Surface Treatment Document And Classification:	C-123 Mfr Ref Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523P4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.