

Description

diameter: 1/8", grip range: 0.251" - 0.312", universal head, monel sleeve, 15-7 ph corrosion resistant stem, sleeve has aluminum coating (p)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | CR3523P405 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-613-4477 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N CR3523P4-05 Specifications

| | |
|----------------------|---|
| Fastener Length: | 0.412 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Nominal |
| Shank Diameter: | 0.126 Inches Nominal |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.250 Inches Nominal |
| Material: | Nickel Alloy Sleeve |
| Material: | Steel Corrosion Resisting Mechanical Lock |
| Material: | Steel Corrosion Resisting Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523P4-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.