

Description

diameter: 5/32", grip range: 0.313" - 0.375", universal head, monel sleeve, 15-7 ph corrosion resistant stem, sleeve has aluminum coating (p)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3523P506
Minimum Qty (MOQ):	100
NSN:	5320-01-222-0138
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N CR3523P5-06 Specifications

Fastener Length:	0.450 Inches Minimum And 0.480 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Break Stem
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Special Features:	Min Blind Clearance 0.370/hole Limits 0.160-0.164
Material:	Nickel Alloy R-405 Sleeve
Material:	Iron Alloy 660 Locking Ring
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std 2nd Material Response Stem
Material Document And Classification:	Ams 5731 Assn Std 3rd Material Response Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec 1st Material Response Sleeve
Surface Treatment:	Aluminum Sleeve
Surface Treatment Document And Classification:	C-123 Mfr Ref Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523P5-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.