

Description

diameter: 5/32", grip range: 0.376" - 0.437", universal head - monel sleeve - 15-7 ph corrosion resistant stem- sleeve has aluminum coating (p)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3523P507
Minimum Qty (MOQ):	100
NSN:	5320-01-353-6933



P/N CR3523P5-07 Specifications

Fastener Length:	0.543 Inches Nominal
Head Style:	Universal
Head Height:	0.057 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Material:	Iron Alloy 660 Locking Ringnickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3523P5-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.