

**Description**

diameter: 5/32", grip range: 0.126" - 0.187", nas1097, flush head, monel sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3524-5-3](#)

SKU / Model:	CR3524503
Minimum Qty (MOQ):	100
NSN:	5320-01-337-5804
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N CR3524-5-03 Specifications

<b>Fastener Length:</b>	0.293 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.156 Inches Minimum And 0.160 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.203 Inches Minimum And 0.235 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Sleeve
<b>Specification/standard Data:</b>	80205-nas9309 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3524-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.