

**Description**

diameter: 5/32", grip range: 0.188" - 0.250", nas1097, flush head, monel sleeve, 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3524-5-4](#)

SKU / Model:	CR3524504
Minimum Qty (MOQ):	100
NSN:	5320-01-164-1678
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N CR3524-5-04 Specifications

<b>Fastener Length:</b>	0.325 Inches Minimum And 0.355 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.156 Inches Minimum And 0.160 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.247 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Nickel Alloy 400 Sleeve
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3524-5-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.