

Description

diameter: 5/32", grip range: 0.251" - 0.312", flush head, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3524-5-5](#)

| | |
|-------------------------|--|
| SKU / Model: | CR3524505 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-164-1679 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N CR3524-5-05 Specifications

| | |
|--|--|
| Fastener Length: | 0.388 Inches Minimum And 0.418 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.156 Inches Minimum And 0.160 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.247 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Nickel Alloy 400 Sleeve |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3524-5-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.