

Description

diameter: 3/16", grip range: 0.126" - 0.187", flush head, monel sleeve, corrosion resistant stem, CR3524 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3524-6-3](#)

| | |
|-------------------------|-----------------------|
| SKU / Model: | CR3524603 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-337-5805 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



* See page 2 for technical characteristics

P/N CR3524-6-03 Specifications

| | |
|--|--|
| Fastener Length: | 0.325 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.188 Inches Minimum And 0.192 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.259 Inches Minimum And 0.291 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Sleeve |
| Specification/standard Data: | 80205-nas9309 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3524-6-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.