

**Description**

diameter: 1/8", grip range: 0.045" - 0.062", flush head, oversized diameter, monel sleeve, 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | CR3552401        |
| Minimum Qty (MOQ): | 100              |
| NSN:               | 5320-01-390-3112 |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N CR3552-4-01 Specifications

|                             |  |
|-----------------------------|--|
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Head Major Diameter:</b> | 0.221 Inches Minimum And 0.229 Inches Maximum                                  |
| <b>Expansion Device:</b>    | Serrated Stem-type W   |
| <b>Countersink Angle:</b>   | 100.0 Degrees Nominal  |
| <b>Material:</b>            | Nickel Alloy Sleeve  |
| <b>Material:</b>            | Steel Corrosion Resisting Locking Ring   |
| <b>Material:</b>            | Steel Corrosion Resisting Stem   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3552-4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.