

## P/N CR3552-4-05

## **Description**

diameter: 1/8", grip range: 0.251" - 0.312", flush head, oversized diameter, monel sleeve, 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

CR3552-4-5

SKU / Model: CR3552405

Minimum Qty (MOQ): 100

NSN: 5320-01-043-6954

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc









<sup>\*</sup> See page 2 for technical characteristics

# P/N CR3552-4-05 Specifications

| Fastener Length:                      | 0.396 Inches Minimum And 0.426 Inches Maximum   |
|---------------------------------------|---|
| Head Style:                           | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)  |
| Shank Diameter:                       | 0.139 Inches Minimum And 0.143 Inches Maximum   |
| Shank Style:                          | Self-plugging Mechanically Locked Stem  |
| Head Major Diameter:                  | 0.221 Inches Minimum And 0.229 Inches Maximum   |
| Expansion Device:                     | Serrated Stem-type W  |
| End Item Identification:              | 8aircraft, T-38; Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Aircraft, F-111; Aircraft, Galaxy C-5; Aircraft, Hercules C-130; Aircraft, Phantom F-4; Aircraft, Eagle F-15; Aircraft, Stratofortress B-52; Aircraft, T-37; Aircraft, Thunderbolt Ii, A-10 |
| Grip Length:                          | 0.251 Inches Minimum And 0.312 Inches Maximum   |
| Countersink Angle:                    | 98.5 Degrees Minimum And 101.5 Degrees Maximum  |
| Material:                             | Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve  |
| Material:                             | Steel Comp 632 Stem   |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem   |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Sleeve   |
| Specification/standard Data:          | 81349-mil-r-7885/9 Government Specification   |
| Nondefinitive Spec/std Data:          | 1 Type And B Style And 2 Class  |

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR3552-4-05">https://military-fasteners.com/rivets/blind+rivets/CR3552-4-05</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR3552-4-05">https://military-fasteners.com/rivets/blind+rivets/CR3552-4-05</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR3552-4-05">https://military-fasteners.com/rivets/blind+rivets/CR3552-4-05</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR3552-4-05">https://military-fasteners.com/rivets/blind+rivets/CR3552-4-05</a> and selecting the quantity you want then