

Description

diameter: 1/8", grip range: 0.313" - 0.375", 100° , flush head - oversized diameter - monel sleeve - 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3552406
Minimum Qty (MOQ):	100
NSN:	5320-01-043-5862
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3552-4-06 Specifications

Fastener Length:	0.458 Inches Minimum And 0.488 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Specification/standard Data:	81349-mil-r-7885/9 Government Specification
Nondefinitive Spec/std Data:	1 Type And B Style And 2 Class

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3552-4-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.