

Description

diameter: 5/32", grip range: 0.188" - 0.250", flush head, oversized diameter, monel sleeve, corrosion resistant stem, CR3552 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3552-5-4](#)

SKU / Model:	CR3552504
Minimum Qty (MOQ):	100
NSN:	5320-01-043-1927
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3552-5-04 Specifications

Fastener Length:	0.361 Inches Minimum And 0.381 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Lubrication On Stem Only
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material:	Steel Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3552-5-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.