

Description

diameter: 5/32", grip range: 0.251" - 0.312", flush head, oversized diameter, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3552-5-5](#)

SKU / Model:	CR3552505
Minimum Qty (MOQ):	100
NSN:	5320-01-043-1928
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR3552-5-05 Specifications

Fastener Length:	0.404 Inches Minimum And 0.434 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Aircraft, Phantom F-4;aircraft, Eagle F-15;aircraft, Galaxy C-5;aircraft, B-1b;aircraft, Stratofortress B-52;aircraft, Thunderbolt II, A-10;aircraft,f-111;aircraft, T-37;aircraft, Hercules C-130;aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Specification/standard Data:	81349-mil-r-7885/9 Government Specification
Nondefinitive Spec/std Data:	1 Type And B Style And 2 Class

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3552-5-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.