

P/N CR3552-5-9

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: CR355259

Minimum Qty (MOQ): 100

NSN: 5320-01-043-0677

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



^{*} See page 2 for technical characteristics

P/N CR3552-5-9 Specifications

Fastener Length:	0.654 Inches Minimum And 0.684 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Aircraft, Stratofortress B-52, Aircraft, F-111
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Specification/standard Data:	81349-mil-r-7885/9 Government Specification
Nondefinitive Spec/std Data:	1 Type And B Style And 2 Class

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3552-5-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.