

**Description**

diameter: 3/16", grip range: 0.188" - 0.250", flush head, oversized diameter, monel sleeve, corrosion resistant stem, CR3552 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3552-6-4](#)

SKU / Model:	CR3552604
Minimum Qty (MOQ):	100
NSN:	5320-01-043-5866
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3552-6-04 Specifications

<b>Fastener Length:</b>	0.380 Inches Minimum And 0.400 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.201 Inches Minimum And 0.205 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.357 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>End Item Identification:</b>	9helicopter, Cobra/tow, Ah Series;aircraft, Ac-130h, Mc-130h, Ec-130;aircraft, Phantom F-4;aircraft, F-111;aircraft, B-1b;aircraft, Eagle F-15;aircraft, Stratofortress B-52;helicopter, Uh-60a/uh-60d;aircraft, Galaxy C-5;aircraft, Thunderbolt II, A-10
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Lubrication On Stem Only
<b>Material:</b>	Nickel Alloy 400 Body Or Nickel Alloy R-405 Body
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Body

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3552-6-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.