

Description

diameter: 3/16", grip range: 0.188" - 0.250", flush head, oversized diameter, monel sleeve, corrosion resistant stem, CR3552 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3552-6-4](#)

| | |
|-------------------------|---|
| SKU / Model: | CR3552604 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-043-5866 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3552-6-04 Specifications

| | |
|--|--|
| Fastener Length: | 0.380 Inches Minimum And 0.400 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.201 Inches Minimum And 0.205 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.357 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| End Item Identification: | 9helicopter, Cobra/tow, Ah Series;aircraft, Ac-130h, Mc-130h, Ec-130;aircraft, Phantom F-4;aircraft, F-111;aircraft, B-1b;aircraft, Eagle F-15;aircraft, Stratofortress B-52;helicopter, Uh-60a/uh-60d;aircraft, Galaxy C-5;aircraft, Thunderbolt II, A-10 |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Lubrication On Stem Only |
| Material: | Nickel Alloy 400 Body Or Nickel Alloy R-405 Body |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Body |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3552-6-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.