

## Description

diameter: 3/16", grip range: 0.188" - 0.250", flush head, oversized diameter, monel sleeve, corrosion resistant stem, CR3552 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[CR3552-6-4](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR3552604                                   |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-043-5866                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N CR3552-6-04 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.380 Inches Minimum And 0.400 Inches Maximum  |
| <b>Head Style:</b>                           | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)   |
| <b>Shank Diameter:</b>                       | 0.201 Inches Minimum And 0.205 Inches Maximum  |
| <b>Shank Style:</b>                          | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                  | 0.357 Inches Maximum   |
| <b>Expansion Device:</b>                     | Serrated Stem-type W   |
| <b>Lubrication:</b>                          | Dry Film   |
| <b>End Item Identification:</b>              | 9helicopter, Cobra/tow, Ah Series;aircraft, Ac-130h, Mc-130h, Ec-130;aircraft, Phantom F-4;aircraft, F-111;aircraft, B-1b;aircraft, Eagle F-15;aircraft, Stratofortress B-52;helicopter, Uh-60a/uh-60d;aircraft, Galaxy C-5;aircraft, Thunderbolt II, A-10 |
| <b>Grip Length:</b>                          | 0.188 Inches Minimum And 0.250 Inches Maximum  |
| <b>Countersink Angle:</b>                    | 100.0 Degrees Nominal  |
| <b>Special Features:</b>                     | Lubrication On Stem Only   |
| <b>Material:</b>                             | Nickel Alloy 400 Body Or Nickel Alloy R-405 Body   |
| <b>Material:</b>                             | Steel Comp 632 Stem  |
| <b>Material Document And Classification:</b> | Ams 5657 Assn Std Single Material Response Stem  |
| <b>Material Document And Classification:</b> | Qq-n-281 Fed Spec All Material Responses Body  |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3552-6-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.