

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | CR355266 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-043-1933 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3552-6-6 Specifications

| | |
|--|--|
| Fastener Length: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.200 Inches Minimum And 0.204 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.349 Inches Minimum And 0.357 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| End Item Identification: | Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Aircraft, Phantom F-4, Aircraft, Stratofortress B-52, Aircraft, Eagle F-15, Aircraft, B-1b, Aircraft, F-111 |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Sleeve |
| Specification/standard Data: | 81349-mil-r-7885/9 Government Specification |
| Nondefinitive Spec/std Data: | 1 Type And B Style And 2 Class |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3552-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.