

**Description**

Fastener Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3552-6-08](#)

|                         |  |
|-------------------------|--|
| SKU / Model:            | CR355268   |
| Minimum Qty (MOQ):      | 100  |
| NSN:                    | 5320-01-043-3485                                 |
| Schedule B:             | 7318.23.0000                                     |
| ECCN:                   | EAR99  |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3552-6-8 Specifications

|  |   |
|--|---|
| <b>Fastener Length:</b>                      | 0.548 Inches Minimum And 0.578 Inches Maximum   |
| <b>Head Style:</b>                           | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)  |
| <b>Shank Diameter:</b>                       | 0.200 Inches Minimum And 0.204 Inches Maximum   |
| <b>Shank Style:</b>                          | Self-plugging Mechanically Locked Stem  |
| <b>Head Major Diameter:</b>                  | 0.349 Inches Minimum And 0.357 Inches Maximum   |
| <b>Expansion Device:</b>                     | Serrated Stem-type W  |
| <b>End Item Identification:</b>              | W/s: Aircraft, Stratofortress B-52; Aircraft, Phantom F-4; Aircraft, B-1b; Aircraft, Eagle F-15; Aircraft, F-16; Aircraft, Hx Unique; Aircraft, Thunderbolt II, A-10; Aircraft, F-111 |
| <b>Grip Length:</b>                          | 0.438 Inches Minimum And 0.500 Inches Maximum   |
| <b>Countersink Angle:</b>                    | 98.5 Degrees Minimum And 101.5 Degrees Maximum  |
| <b>Material:</b>                             | Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve  |
| <b>Material:</b>                             | Steel Comp 632 Stem   |
| <b>Material Document And Classification:</b> | Ams 5657 Assn Std Single Material Response Stem   |
| <b>Material Document And Classification:</b> | Qq-n-281 Fed Spec All Material Responses Sleeve   |
| <b>Specification/standard Data:</b>          | 81349-mil-r-7885/9 Government Specification   |
| <b>Nondefinitive Spec/std Data:</b>          | 1 Type And B Style And 2 Class  |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3552-6-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.