

Description

diameter: 1/8", grip range: 0.438" - 0.50", universal head, oversized diameter, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3553-4-8](#)

SKU / Model:	CR3553408
Minimum Qty (MOQ):	100
NSN:	5320-01-042-2892
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



P/N CR3553-4-08 Specifications

Fastener Length:	0.578 Inches Minimum And 0.598 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Special Features:	Lubrication On Stem Only
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material:	Steel Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-4-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.