

Description

Blind Rivet 5320-01-042-2894 Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3553-4-04](#)

SKU / Model:	CR355344
Minimum Qty (MOQ):	100
NSN:	5320-01-042-2894
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3553-4-4 Specifications

Fastener Length:	0.328 Inches Minimum And 0.348 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
End Item Identification:	W/s:aircraft, Phantom F-4; Helicopter, Iroquois Uh-1; Aircraft, Eagle F-15; Aircraft, Delta Dart F-106; Aircraft, Galaxy C-5; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter Observation (ahip), Oh-58d; Helicopter, Iroquois Hh/uh-1; Aircraft, Stratofortress
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Special Features:	Lubrication On Stem Only
Material:	Nickel Alloy 400 Body Or Nickel Alloy R-405 Body
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Body

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-4-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.