

**Description**

diameter: 5/32", grip range: 0.031" - 0.062", universal head, oversized diameter, monel sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3553-5-1](#)

SKU / Model:	CR3553501
Minimum Qty (MOQ):	100
NSN:	5320-01-288-0889
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3553-5-01 Specifications

<b>Fastener Length:</b>	0.173 Inches Minimum And 0.203 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.031 Inches Minimum And 0.062 Inches Maximum
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Specification/standard Data:</b>	81349-mil-r-7885/8 Government Specification
<b>Nondefinitive Spec/std Data:</b>	1 Type And B Style And 1 Class

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-5-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.