

Description

CR3553-5-02 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3553-5-2](#)

SKU / Model:	CR3553502
Minimum Qty (MOQ):	100
NSN:	5320-01-288-0890
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

P/N CR3553-5-02 Specifications

Fastener Length:	0.216 Inches Minimum And 0.246 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams5657 Assn Std Single Material Response Stem
Specification/standard Data:	81349-mil-r-7885/8 Government Specification
Nondefinitive Spec/std Data:	1 Type And B Style And 1 Class

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.