

**Description**

diameter: 5/32", grip range: 0.126" - 0.187", universal head, oversized diameter, monel sleeve, 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3553-5-3](#)

SKU / Model:	CR3553503
Minimum Qty (MOQ):	100
NSN:	5320-01-041-6453
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N CR3553-5-03 Specifications

<b>Fastener Length:</b>	0.299 Inches Minimum And 0.319 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>End Item Identification:</b>	Wsd: Aircraft, Galaxy C-5; Aircraft, Eagle F-15; Helicopter, Iroquois Hh/uh-1; Aircraft, Thunderbolt Ii, A-10; Aircraft, Freedom Fighter F-5; Aircraft, Hercules C-130; Aircraft, Starlifter C-141; Aircraft, F-111; Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Aircraft, Phantom F-4
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Criticality Code Justification:</b>	Feat
<b>Special Features:</b>	Weapon System Essential
<b>Material:</b>	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
<b>Material:</b>	Steel Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.